PLATE 9 OF 24

EXPLANATION

SOUTHWEST BOARS TUSK QUADRANGLE

WYOMING-SWEETWATER CO.

OVERBURDEN ISOPACHS - Showing thickness of overburden, in feet, from surface to top of coal bed. Dashed where vertical accuracy possibly not within 40 feet. Isopach interval 100 feet (31 m) over strippable coal and 200 feet (61 m) beyond the stripping-limit line.

0 211

DRILL HOLE - Showing thickness of overburden, in feet, from surface to top of coal bed.

MINING-RATIO CONTOUR - Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in areas underlain by coal of Reserve Base thickness within the stripping-limit (in this quadrangle, the 200-foot-overburden isopach). To convert mining ratio to cubic meters of overburden per metric ton of recoverable coal, multiply mining ratio by 0.8428.

-----15-----

RS-9 - Rock Springs No. 9


COAL BED SYMBOL AND NAME

----RS-9----

TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Short dashed where inferred by present

TRACE OF FAULT - Bar and ball on down-thrown side when direction of movement is known. Dashed where inferred or approxi-mately located.

To convert feet to meters, multiply feet



UNITED STATES

COAL RESOURCE OCCURRENCE MAP OF THE SOUTHWEST QUARTER OF THE BOARS TUSK 15-MINUTE QUADRANGLE, SWEETWATER COUNTY, WYOMING

> BY DAMES & MOORE 1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.